

DECLARATION OF PERFORMANCE SUMMER

n° CPR_01

- Unique identification code of the product type: **Dry-pressed ceramic tiles, with water absorption $E_v \leq 0,5\%$**
- Intended uses: **for internal and external walls and floorings**
- Name or registered trade mark, and contact address of the manufacturer:
Fap ceramiche, via Ghiarola Nuova, 44 – 41042 Fiorano Modenese (MO) ITALY
- System(s) of assessment and verification of constancy of performance (AVCP): **System 4**
- Name and identification number of notified laboratory, if relevant: **not relevant**
- Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1FL/A1	EN 14411: 2012
Release of dangerous substance: (only for GL ceramic tiles)		
- Cadmium	npd	
- Lead	npd	
Breaking strenght (thickness $\geq 7,5$)	≥ 1300 N	
Breaking strenght (thickness $< 7,5$)	≥ 700 N	
Slipperiness	See table attached	
Tactility	npd	
Bond strenght/adhesion	npd	
Thermal shock resistance	Pass	
Durability for	Pass	
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Tabella - Scivolosità rev.20/07/2020				
Serie	Prodotto	DIN 51130 (DE)	BCRA D.M. 236/1989 (ITA)	D.B. SUA 3/2006 (ESP)
SUMMER	Sale R10	R10	npd	npd
	Sabbia R10	R10	npd	npd
	Terracotta R10	R10	npd	npd
	Vento R10	R10	npd	npd
	Sciara R10	R10	npd	npd
	Brezza R10	R10	npd	npd
	Crepuscolo R10	R10	npd	npd

Signed for and on behalf of the manufacturer by:

Luca Mussini
President

Fiorano Modenese 20/07/2020



Via Ghiarola Nuova, 44 - 41042 Fiorano Modenese (MO) Italy
 tel. +39 0536 837511 - fax estero +39 0536 837542
 www.fapceramiche.com info@fapceramiche.com