



SPECIFICATIONS – ROMA DIAMOND (porcelain stoneware)	
Supply of <b>FAP ceramiche</b> porcelain stoneware wall and floor tiles.	
Product and process features	
<p>FAP unglazed porcelain stoneware wall and floor tiles, vitrified full body with added feldspar, quartz and kaolin, obtained by pressing (450 kg/cm<sup>2</sup> and above) the atomised body and then sintering at a temperature of approx. 1250 °C.</p> <p>The full vitrification of the tiles ensures an average absorption of 0.08%, well below the level set in European standard ISO 10545-3.</p> <p>The product is therefore compact, frost-proof, resistant to knocks and physical and chemical aggression, bending and differences in temperature.</p>	
Conformity to standards ISO 13006 - EN 14411, Annex G	
The <b>ROMA DIAMOND</b> porcelain stoneware collection complies with all ISO 13006 and EN 14411 standards (Annex G Group BIa E <sub>v</sub> ≤0,5%).	
Green certifications	
<p><b>FAP ceramiche</b> is a member of the U.S. Green Building Council. LEED compliant, the <b>ROMA DIAMOND</b> porcelain stoneware collection can help to obtain between 1 and 7 LEED credits, depending on the colour and use.</p>	
Commercial product description	
COMPANY	FAP ceramiche
COLLECTION	Roma Diamond (porcelain stoneware)
SIZES (cm)	120x278 RT MAXXI, 120x120 RT, 75x150 RT, 75x75 RT, 60x60 RT
THICKNESS (mm)	6 (120x278 RT MAXXI), 9 (120x120 RT, 60x60 RT), 9,5
FINISHES	Brilliant

