

DECLARATION OF PERFORMANCE COLLECTION DESERT

n° CPR_01

1. Unique identification code of the product type: **Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$**
2. Intended uses: **for internal and external walls and floorings**
3. Name or registered trade mark, and contact address of the manufacturer:
Fap ceramiche, via Ghiarola Nuova, 44 – 41042 Fiorano Modenese (MO) ITALY
4. System(s) of assessment and verification of constancy of performance (AVCP): **System 4**
5. Name and identification number of notified laboratory, if relevant: **not relevant**
6. Declared performance

Essential Characteristics	Performance	Harmonised technical specification
Reaction to fire	A1FL/A1	EN 14411: 2012
Release of dangerous substance: (only for GL ceramic tiles)		
- Cadmium	npd	
- Lead	npd	
Breaking strenght (thickness $\geq 7,5$)	≥ 1300 N	
Breaking strenght (thickness $< 7,5$)	≥ 700 N	
Slipperiness	See table attached	
Tactility	npd	
Bond strenght/adhesion	npd	
Thermal shock resistance	Pass	
Durability for	Pass	
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Norberto Marzani
Marketing Manager

Fiorano Modenese 10/04/2016

Tabella - Scivolosità rev.12/09/2016

Serie	Prodotto	DIN 51130 (DE)	BCRA D.M. 236/1989 (ITA)	D.B. SUA 3/2006 (ESP)
Desert	Beige matt	R9	> 0,40	npd
	Beige Out	R11	> 0,40	npd
	Deep matt	R9	> 0,40	npd
	Deep Out	R11	> 0,40	npd
	Warm matt	R9	> 0,40	npd
	Warm Out	R11	> 0,40	npd
	White matt	R9	> 0,40	npd
	White Out	R11	> 0,40	npd