

## DECLARATION OF PERFORMANCE MILANO & FLOOR

n° CPR\_01

1. Unique identification code of the product type: **Dry-pressed ceramic tiles, with water absorption  $E_v \leq 0,5\%$**
2. Intended uses: **for internal and external walls and floorings**
3. Name or registered trade mark, and contact address of the manufacturer:  
**Fap ceramiche, via Ghiarola Nuova, 44 – 41042 Fiorano Modenese (MO) ITALY**
4. System(s) of assessment and verification of constancy of performance (AVCP): **System 4**
5. Name and identification number of notified laboratory, if relevant: **not relevant**
6. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1FL/A1	EN 14411: 2012
Release of dangerous substance: (only for GL ceramic tiles)		
- Cadmium	npd	
- Lead	npd	
Breaking strenght (thickness $\geq 7,5$ )	$\geq 1300$ N	
Breaking strenght (thickness $< 7,5$ )	$\geq 700$ N	
Slipperiness	See table attached	
Tactility	npd	
Bond strenght/adhesion	npd	
Thermal shock resistance	Pass	
Durability for	Pass	
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

**Luca Mussini**  
**President**

**Fiorano Modenese 22/06/2018**

**Tabella - Scivolosità rev.22/06/2018**

Serie	Prodotto	DIN 51130 (DE)	BCRA D.M. 236/1989 (ITA)	D.B. SUA 3/2006 (ESP)
MILANO & FLOOR	Grigio Matt	R9	npd	npd
	Bianco Matt	R9	npd	npd
	Tortora Matt	R9	npd	npd
	Beige Matt	R9	npd	npd
	Corten matt	R9	npd	npd
	Grigio Satin	npd	npd	npd
	Bianco Satin	npd	npd	npd
	Tortora Satin	npd	npd	npd
	Beige Satin	npd	npd	npd
	Corten Satin	npd	npd	npd