

## SPECIFICATIONS – COLOR>NOW FLOOR (porcelain stoneware)

Supply of **FAP ceramiche** porcelain stoneware floor tiles.

### Product and process features

FAP glazed porcelain stoneware wall and floor tiles, vitrified full body with added feldspar, quartz and kaolin, obtained by pressing (450 kg/cm<sup>2</sup> and above) the atomised body and then sintering at a temperature of approx. 1250 °C.

The full vitrification of the tiles ensures an average absorption of 0.08%, well below the level set in European standard ISO 10545-3.

The product is therefore compact, frost-proof, resistant to knocks and physical and chemical aggression, bending and differences in temperature.

### Conformity to standards ISO 13006 - EN 14411, Annex G

The **COLOR>NOW FLOOR** porcelain stoneware collection complies with all ISO 13006 and EN 14411 standards (Annex G Group B1a E<sub>b</sub> ≤0,5%).

### Green certifications

**FAP ceramiche** is a member of the U.S. Green Building Council. LEED compliant, the **COLOR>NOW FLOOR** porcelain stoneware collection can help to obtain between 1 and 7 LEED credits, depending on the colour and use.

### Commercial product description

COMPANY	FAP ceramiche
COLLECTION	COLOR>NOW FLOOR (porcelain stoneware)
SIZES (cm)	60x60 RT
THICKNESS (mm)	9,5 mm
FINISHES	matt